

CHECKLIST FOR OH-STL MIK

21.6.2016 / MA

BEFORE START

PREFLIGHT CHECKS.....	COMPLETED
BAGGAGE AND TOW BAR.....	SECURED
REQUIRED DOCUMENTS.....	ONBOARD
EMERGENCY FUEL VALVE.....	NORMAL/SECURED
POWER LEVER.....	IDLE
PARKING BRAKE.....	SET
ALTERNATE AIR.....	CLOSED
ELECTRIC MASTER (start key).....	OFF
AVIONIC MASTER.....	OFF
ESSENTIAL BUS.....	OFF
ALTERNATE STATIC.....	CLOSED
VOTER SWITCH.....	AUTO
FUEL PUMPS.....	OFF
ENGINE MASTER.....	OFF
ALL LIGHT SWITCHES.....	OFF
HORIZON EMERGENCY SWITCH.....	OFF/GUARDED
ELT.....	ARMED
CIRCUIT BREAKERS.....	CHECKED IN
FLAP SELECTOR.....	UP
PITOT HEAT.....	OFF
FUEL TRANS.....	OFF
ELECTRIC MASTER (start key).....	ON (check avionic fan noise)
RUDER PEDALS.....	ADJUSTED AND LOCKED
PASSENGERS.....	INSTRUCTED
SEATBELTS.....	FASTENED
REAR DOOR.....	CLOSED AND LATCHED
FRONT CANOPY.....	POSITION 1 OR 2
G1000.....	POWERED AND ACKNOWLEDGED
• MFD FUEL QUANTITY CHECKED, RESET/SET IF REQUIRED	
• FUEL TEMPERATURE.....	CHECKED
• TOTAL TIME IN SERVICE	NOTED
• MFD	ENGINE-SYSTEM, ENGINE-DEFAULT

ENGINE START

STROBE.....	ON
POWER LEVER.....	CHECK IDLE
ENGINE MASTER ON (annunciations/engine instruments checked)	
GLOW INDICATION.....	OFF
PROPELLER AREA.....	CLEAR
ELECTRIC MASTER (start key).....	START
OIL PRESSURE.....	OUTSIDE RED WITHIN 3 SECONDS
ANNUNCiations/ENGINE INSTRUMENTS	CHECKED
VOLTAGE, ELECTRICAL LOAD.....	CHECKED
IDLE RPM.....	CHECK 710 ± 30 RPM
PITOT HEAT.....	ON, ANNUNCiations+AMPS CHECKED, OFF

MAX POWER 50% UNTIL ENGINE TEMPERATURES IN GREEN RANGE

BEFORE TAXI

AVIONIC MASTER.....	ON
FMS SETUP	
• Initialize (AUX 4, MAP)	
• Flight plan	
• Radios (COM, NAV, ADF, DME, CDI, BRG 1,2)	
• Performance (speed bugs)	
AUTOPilot TEST	
• DISCONN press, check electric trim not working	
• AP ON, check annunciations and overpowering	
• DISCONN press, check AP off, observe disconnect tone	
INSTRUMENT LIGHT, FLOOD LIGHT.....	AS REQUIRED
POSITION LIGHTS.....	AS REQUIRED
FLAPS.....	FULL TRAVEL, THEN T/O
ALTIMETERS (3: STDBY,PFD,AP).....	SET + COMPARED
STANDBY HORIZON.....	CHECKED
TRANSPOndER.....	CODE /MODE CHECKED

TAXIING

TAXI LIGHT.....	AS REQUIRED
PARKING BRAKE.....	RELEASE
DURING TAXI.....	CHECK BRAKES AND FLIGHT INSTRUMENTS

BEFORE TAKE-OFF

PARKING BRAKE.....	SET
SEAT BELTS.....	FASTENED
REAR DOOR.....	CLOSED+LATCHED
FRONT CANOPY.....	CLOSED+LATCHED
DOOR WARNING	OFF
CIRCUIT BRAKERS.....	CHECKED
FLAPS.....	CHECK T/O
ELECTRIC ELEVATOR TRIM.....	CHECK T/O
FLIGHT CONTROLS	FREE MOVEMENT, CORRECT SENSE
POWER LEVER.....	IDLE
ENGINE INSTRUMENTS.....	GREEN RANGE CHECKED
VOTER SWITCH.....	A, AUTO, B, AUTO
ECU TEST.....	PERFORM
POWER LEVER.....	MAX FOR 10 SECONDS
• ANNUNCIATIONS.....	CHECK OK/NORMAL RANGE
• INSTRUMENTS.....	CHECK WITHIN NORMAL RANGE
• LOAD (OAT 0–20°C).....	MIN 96% (RPM 2200-2300)
TAKE-OFF BRIEFING.....	PERFORMED
PITOT HEAT.....	AS REQUIRED
CIRCUIT BREAKERS.....	CHECKED

LINE-UP

TRANSPONDER.....	CHECKED
FUEL PUMPS.....	ON
LANDING LIGHT, POSITION LIGHTS.....	ON/AS REQUIRED
PARKING BRAKE.....	RELEASE

AFTER TAKEOFF

FLAPS.....	UP
CLIMB POWER (MAX 92% OR MAX 2100 RPM).....	SET
FUEL PUMPS.....	OFF

CRUISE

POWER LEVER.....	65–75%
ENGINE INSTRUMENTS.....	MONITOR
FUEL TRANSFER.....	AS REQUIRED

APPROACH

ALTIMETERS (3)	SET
EXTERIOR LIGHTS.....	AS REQUIRED
AUTOPilot.....	OFF
FUEL PUMPS.....	ON

AFTER LANDING

FLAPS.....	UP
PITOT HEAT.....	OFF
ALTERNATE AIR.....	CLOSED
FUEL PUMPS.....	OFF
LANDING/TAXI LIGHT.....	AS REQUIRED
TRANSPOndER.....	AS REQUIRED

ENGINE SHUTDOWN

PARKING BRAKE.....	SET
POWER LEVER	IDLE
ELT.....	121,500 CHECKED
MFD ENGINE-SYSTEM.....	CHECK
MFD ENGINE-FUEL TTL TIME.....	NOTED
AVIONIC MASTER	OFF
LIGHTS EXCEPT STROBE.....	OFF
<u>VERIFY ENGINE OIL TEMP MAX 92 °C BEFORE SHUTDOWN</u>	
ENGINE MASTER.....	OFF
STROBE.....	OFF
<u>WHEN ENGINE INDICATIONS X-OUT RED:</u>	
ELECTRIC MASTER (start key).....	OFF
START KEY.....	REMOVED

OH-STL SPEEDS	1000 kg	1100 kg	1280 kg
ROTATE	58 KIAS	61 KIAS	67 KIAS
Vx (FLAPS T/O)	65 KIAS	67 KIAS	72 KIAS
Vy	72 KIAS	72 KIAS	72 KIAS
APPROACH (LDG)	68 KIAS	72 KIAS	77 KIAS

FLAPS: T/O 110, LDG 98
 MAX FUEL UNBALANCE: 9 GALLONS